


MSDS - Clear-Lay™ Rigid PVC Film



Page 1 of 2

Emergency Contact:

Grafix
5800 Pennsylvania Ave.
Maple Heights, OH 44137
(216) 581-9050

Product Identification:

Clear-Lay is an Polyvinyl Chloride film. Various fillers or additives used to modify the physical appearance and/or surface properties may be present. Actual formula is proprietary.

Hazardous Ingredients:

This material is not a "health hazard" as defined under the OSHA Hazard Communication Standard, 29 CFR 1910.1200 or S.A.R.A. Title III, Section 313. This material is considered an article under OSHA and TSCA standards.

Physical-Chemical Data:

The transparent to opaque, odorless film is chemically stable and resistant to water. It has a specific gravity of 1.32 - 1.45.

Physical Hazards:

Heavy gauges of PVC Film can contain sharp edges. Proper protective gear such as gloves is recommended. The top coating of the film can create a slip hazard when dropped on the floor. Walking areas should be kept clear of this film.

Unwinding, winding and passage of this film through and over rollers will tend to generate a strong electrostatic charge on the web. Static discharge devices should be properly positioned at such points to eliminate the charge and prevent uncontrolled discharge from the web. This is particularly required in potentially explosive atmospheres and to protect personnel from the effects of static discharge.

General exhaust is acceptable except where overheating can occur during processing. High temperature are not recommended.

Grafix


5800 Pennsylvania Ave. Maple Heights, OH 44137

(800) 447-2349 (216) 581-9050 Fax (216) 581-9041

E-mail: info@grafixarts.com Web: www.grafixarts.com



MSDS - Clear-Lay™ Rigid PVC Film



Page 2 of 2

Health Hazard Data:

No adverse health effect have been attributed to this PVC film at ambient temperature.

Hazard Designations

		Key
Health:	1	0-None
Flamability	1	1-Slight
Reactivity	0	2-Moderate
		3-Severe
		4-Extreme

Control Measure and Safe Handling Procedures

The film will burn if exposed to flame. Fire fighters should protect themselves from decomposition and combustion products that may include carbon dioxide, carbon monoxide, HCL and other such toxic gases. Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to products of combustion exist. Fire fighting extinguishing media include carbon dioxide, water spray, foam or dry chemical.

Disposal and Shipping Information:

PVC film is not classified as hazardous waste under the Resource Conservation and Recovery Act, and unless prohibited by state or local regulation, can be disposed of in a municipal landfill or incinerated. This product is not classified by the U.S. Department of Transportation as a hazardous material.

Information Contact:

Grafix
5800 Pennsylvania Ave.
Maple Heights, OH 44137

To the best of our knowledge the information contained herein is accurate. However, Grafix assumes no liability whatsoever, for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All material may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

Grafix

5800 Pennsylvania Ave. Maple Heights, OH 44137

(800) 447-2349 (216) 581-9050 Fax (216) 581-9041

E-mail: info@grafixarts.com Web: www.grafixarts.com

